

Specification of EXP40

V1.1

Revision Record

Version	Date	Author	Contents
V1.0	2011-3-31	Anne	
V1.1	2011-4-2	Anne	

Extension Module for IP652 (EXP40)

The Intelligent Communication Device for Next Generation Network

Specification



EXP40



IP652 with EXP40

Keys	<ul style="list-style-type: none"> 40 multi-functional key with dual-color LED
Power Supply	<ul style="list-style-type: none"> 5V/1A Power Adapter or IP652
Key Feature	<ul style="list-style-type: none"> 40 multi-functional key can be used as speed dial, BLF, shortcut Key, pick up , call park Daisy chain for 6 EXP40 at Max. 260 multi-functional keys at Max.
Protocols	<ul style="list-style-type: none"> SIP V2 (RFC 3261,3262,3263,3264) Backward Compatible with RFC2543

LED	<ul style="list-style-type: none"> 40 Red-Green dual-color LEDs used to indicate multi-functional key status
I/O Interfaces	<ul style="list-style-type: none"> 2 RJ11 Jack for extension module connection
Environmental	<ul style="list-style-type: none"> Operation Temperature: 0~50 Degree C Storage Temperature: -25~ 85 Degree C Relative Humidity: 10%~90% No Condensing Shock: Up to 75cm (30 inches) Drop upon Package
Dimension	<ul style="list-style-type: none"> (L)167mm X (W)132mm X (H)51mm 240g

Copy Right 2011 All Rights Reserved by EASY3CALL TECHNOLOG LIMITED V1.1

Revision time: 2011-4-2 10:30